



## Standard 24VDC Interface Board KTP-CB600-T23 Series

### Product Specification

● Board type	KTP-CB602-T23	KTP-CB609-T23	KTP-CB609-T23/640
● Printer type	Fujitsu FTP-602 series	Fujitsu FTP-609 series	Fujitsu FTP-609 series
● Interface	RS232C & USB	RS232C & USB	RS232C & USB
● Operating power	24VDC	24VDC	24VDC
● Current peak	approx. 2,3A	approx. 3,5A	approx. 4,0A
● Head configuration	448/576dots/line	432/576dots/line	640dots/line
● Eff. printing width	56/72mm	54/72mm	80mm
● Baud rate	9.600 standard, max. 115.200	9.600 standard, max. 115.200	9.600 standard, max. 115.200
● USB 1.1	full speed	full speed	full speed
● Print direction	portrait/landscape/upside down for all printer types		
● Character spacing	20, 16, 14, 12 & 10x22 dots	20, 16, 14, 12 & 10x22 dots	20, 16, 14, 12 & 10x22 dots
● Character addressing	1 byte codepage, 2 byte Unicode	1 byte codepage, 2 byte Unicode	1 byte codepage, 2 byte Unicode
● Character modification	enlarge, emphasise, underline, reverse, italic, sub- superscript		
● Standard font	Codepages 437, available 737, 850, 852, 857, 860, 866, 869, 1252, 1253, 1254		
● Graphic mode	HP PCL5- line graphics	HP PCL5- line graphics	HP PCL5- line graphics
● Label	graphics or text	graphics or text	graphics or text
● Bar code	Code 2/5, Codebar, Code 39, Code 128, EAN 8/13/128, UPCA/E for all printer types		
● Memory	448KB Flash for fonts, logo & download characters		
● Drivers	Windows 2K, XP, Linux CUPS or ASCII Mode with ESC/FS Commands for all printer types		
● Operating temp.	-20°C to +70°C	-20°C to +70°C	- 20°C to +70°C
● Storage temp.	-20°C to +85°C	-20°C to +85°C	-20 °C to +85°C
● Cutter function	full & partial cut	full & partial cut	full or partial cut
● Printing speed	100mm/sec.	200mm/sec.	200mm/sec.
● Mech. dim. (WxD)	60x85mm	60x85mm	60x85mm
● Adapter set	non	ITP-KTP-AS609	ITP-KTP-AS609/640
● Paper detection, head up detection, head temperature detection, label function possible			
● Paper near end function, paper end function			
● Online function for "printer status"			