



Standard 12VDC KIT

KTP-CB609-T24 Series for FTP-609 Series

Product Specification

● Board type	KTP-CB609-T24		
● Printer type	FTP-629 Series	FTP-639Series	FTP-639MCL364
● Operating power	12VDC	12VDC	12VDC
● Current peak	approx. 3,0A	approx. 4,0A	approx. 5,6A
● Paper insertion	rear	rear	rear
● Paper width	60mm	80mm	82,5mm
● Eff. printing width	54mm	72mm	80mm
● Baud rate	9.600 standard, max. 115.200	9.600 standard, max. 115.200	
● USB 1.1	full speed		
● Print direction	portrait/landscape/upside down for all printer types		
● Character spacing	20, 16, 14, 12 & 10x22 dots		
● Character addressing	1 byte codepage, 2 byte Unicode		
● Character modification	enlarge, emphasise, underline, reverse, italic, sub- superscript		
● Standard font	Codepages 437, available 737, 850, 852, 857, 860, 866, 869, 1252, 1253, 1254		
● Graphic mode	HP PCL5- line graphics		
● Label	graphics or text		
● Bar code	Code 2/5, Codebar, Code 39, Code 128, EAN 8/13/128, UPCA/E for all printer types		
● Memory	448KB Flash for fonts, logo & download characters		
● Drivers	Windows 2K, XP, Linux CUPS or ASCII Mode with ESC/FS Commands for all printer types		
● Operating temp.	-20°C to +70°C		
● Storage temp.	-20°C to +85°C		
● Cutter function	full & partial cut		
● Printing speed	100mm/sec.	80mm/sec.	80mm/sec.
● Paper detection, head up detection, head temperature detection, label function possible			
● Paper near end function, paper end function			
● Online function for "printer status"			
● Remarks: cable set is included in the delivery			