

FTP-609 Thermal Printer Series

Features

- Ultra high speed
- Wide paper range
- ELM with lock type
- ELM with cutter
- Multi featuring die-cast frame
- Compact size
- High resolution



Applications

- Kiosk
- Ticket
- Receipts
- Label (scale, courier)
- ATM machines
- Measuring devices
- Medical equipment
- Gaming

GENERAL SPECIFICATION	
Printing method	Direct thermo
Printing resolution (dots/mm)	8
Printing pitch (mm)	0.125 (H) x 0.125 (V)
Printing speed (mm/sec)	200
Operating voltage	24 V
Sensor paper out	Photo interrupter
Sensor head-up	Micro-switch (gold plated)
Sensor head temperature	Thermistor
Option	Auto cutter

MECHANISMS									
Mechanisms	Paper thickness (mm/x)	Paper path	Dots/line	Print speed (mm/sec)	Cutter	Reliability (KM/ M. pulses)	Cutter life (kCuts)	Size W x D x H (mm)	Weight (gr)
FTP-629MCL103	58/150	Curl	432	200	No	100/100	-	82.2x40.5x20.5	110
FTP-629MCL354	58/150	Straight	432	200	Yes	100/100	500	90.6x62.5x37.7	270
FTP-629MCL383	58/150	Curl	432	200	Yes	100/100	500	90.5x70.3x37.4	300
FTP-639MCL054	80/150	Straight	576	200	No	100/100	-	104.2x40.5x20.5	125
FTP-639MCL103	80/150	Curl	576	200	No	100/100	-	104.2x40.5x20.5	125
FTP-639MCL354	80/150	Straight	576	200	Yes	100/100	500	109.7x62.5x37.7	320
FTP-639MCL364	82.5/150	Straight	640	200	Yes	100/100	500	109.7x62.5x37.7	320
FTP-639MCL383	80/150	Curl	576	200	Yes	100/100	500	112.5x70.3x37.4	350
FTP-639MCL393	82.5/150	Curl	640	200	Yes	100/100	500	112.5x70.3x37.4	350